



BLAST HOSE

ART.NR.	MODEL	DESCRIPTION
BLAST HOSE - HEAVY		
Heavy execution, Working Pressure 12 Bar Suitable for all abrasives		
WEAR FACTOR 70 mm³ acc. to DIN 53516		
25060	13 x 7	1/2" 13 mm hose I.D. , 27 mm hose O.D.
25061	19 x 7	3/4" 19 mm hose I.D. , 33 mm hose O.D.
25070	25 x 7	1" 25 mm hose I.D. , 39 mm hose O.D.
25080	32 x 8	1 1/4" 32 mm hose I.D. , 48 mm hose O.D.
25090	38 x 9	1 1/2" 38 mm hose I.D. , 56 mm hose O.D.
25100	42 x 9	1 3/4" 42 mm hose I.D. , 60 mm hose O.D.
25110	50 x 11	2" 50 mm hose I.D. , 72 mm hose O.D.

BLAST HOSE - EXTRA HEAVY		
Extra heavy execution, Working Pressure 12 Bar For sharp-edged hard abrasives, (Aluminium-Oxide, Steel Grit, Glass)		
WEAR FACTOR 50 mm³ acc. to DIN 53516		
25120	13 x 7	1/2" 13 mm hose I.D. , 27 mm hose O.D.
25021	19 x 7	3/4" 19 mm hose I.D. , 33 mm hose O.D.
25130	25 x 7	1" 25 mm hose I.D. , 39 mm hose O.D.
25140	32 x 8	1 1/4" 32 mm hose I.D. , 48 mm hose O.D.
25150	38 x 9	1 1/2" 38 mm hose I.D. , 56 mm hose O.D.
25160	42 x 9	1 3/4" 42 mm hose I.D. , 60 mm hose O.D.
25170	50 x 11	2" 50 mm hose I.D. , 72 mm hose O.D.

- **Temperature range** : -35° C./ +80° C (ambient temperature)
- **Safety factor** : 3,5:1
- **Tube** : NR/SBR/BR, black, smooth, abrasion resistant
- **Reinforcement** : textile, wrapped
- **Cover** : SBR, black, smooth, cloth impression

